

PRODUCT DATA SHEET

Delignit[®]- Industrial Floor Classic / Basic

Base Panel: Construction veneer plywood according to EN 636-2 for the application as a load-bearing building material for interiors, meets **CE 0765-CPR-0420 Blomberger Holzindustrie GmbH, EN 13986, EN 636-2 E1**
CE 0765-CPR-0415 Blomberger Holzindustrie GmbH, EN 13986, EN 636-2 E1

Fire Protection:

	Basic	Classic
Base Panel:	fire resistant, B – s1 – d0 according to DIN EN 13501-1	fire resistant, D – s2 – d0 according to DIN EN 13501-1



Surface:

Antistatic: Human body voltage < 2KV according to DIN IEC 61340-4-1, does not meet the requirements of DIF or ESD

Anti Slip Rating: Slip resistance R9 according to DIN 51130

Reverse Side:

uncolored transparent coating optical veneer quality III / EN 635-2, Film weight approx. 120 g / m², smooth,

Edges:

2mm x 45° Chamfer, uncolored transparent coating offers protection against water splashes but not against standing water.

Specie:

Beech, Brinell Hardness **H_B = 34 N/mm²**, this is significantly superior to other species such as birch (**H_B = 24N/mm²**), when comparing strength, hardness and wear resistance

Bonding:

According to **EN 314-2 (Class 2)** appropriate bonding for wet areas and protected outdoor areas.

Silicon Free:

We assure that the panels do not come in contact with silicone and thus they do not emit silicone.

Dimensions:

2.500 x 1.250 mm, Thickness: 15 / 20 / 25 / 30 mm. Other thicknesses and formats on request.

Machining:

Ready to install, CNC machining according to drawing for a surcharge, based on a workable *.dxf file.

BLOMBERGER HOLZINDUSTRIE GMBH

32817 Blomberg – Deutschland – Postfach 11 53 – Tel.: +49 (0) 5235 / 966-0 – Fax: +49 (0) 5235 / 966-351

w w w . d e l i g n i t . c o m